


# Try-Flex Loop® Expansion Loops & Seismic Connectors



Qty	Pipe Size (in.)	Dimensions (in.)			Pressure (PSI)		Movement Capability					Drain Port (in.)	Wt. (lb.)	Notes
		A	B	C	@ 70° F	@ 200° F	Compression (in.)	Extension (in.)	Parallel (in.)	Rotation "X" Axis (Deg.)	Non-Parallel "Y" Axis (in.)			
	1.25	30.00	18.00	6.75	725	681	2.0	2.0	2.0	15°	1.0	½	6.4	
	1.50	29.00	19.50	6.50	565	531	2.0	2.0	2.0	15°	1.0	½	7.8	
	2.00	32.75	22.25	7.75	500	470	2.0	2.0	2.0	10°	1.0	½	14	
	2.50	36.25	25.00	8.75	400	376	2.0	2.0	2.0	10°	1.0	¾	25	
	3.00	39.25	28.00	9.00	285	267	2.0	2.0	2.0	10°	1.0	¾	35	
	4.00	48.75	33.00	12.00	250	235	2.0	2.0	2.0	5°	1.0	¾	61	
	5.00	61.50	41.25	15.00	200	188	2.0	2.0	2.0	5°	1.0	¾	109	
	6.00	68.63	45.00	18.00	220	206	2.0	2.0	2.0	3°	1.0	¾	149	
	8.00	82.00	53.25	24.00	200	188	2.0	2.0	2.0	ON APPLICATION	1.0	¾	286	
	10.00	99.00	68.38	30.00	200	188	2.0	2.0	2.0	ON APPLICATION	1.0	¾	489	
	12.00	113.00	72.38	36.00	160	150	2.0	2.0	2.0	ON APPLICATION	1.0	¾	713	

PROJECT	
CUSTOMER	
ENGINEER	
REPRESENTATIVE	
DRAWING #	



4560 Buckley Road  
 Liverpool, New York USA 13088-2509  
 315/437-1611 • Fax 315/437-1903  
[www.flexhose.com](http://www.flexhose.com) • 1.877.TRI FLEX