


AssureFlex® Two-Leg U Style Seismic and Expansion Loop for Fire Protection



CSA standard B-51 certified.
Inspected and tested by the
Technical Standards and
Safety Authority of Canada.

QTY.	I.D. (in.)	Length (in.)		Pressure (PSI) @70° F	Drain Port (in.)	Weight (lb.)	Comments
		A (in.)	B (in.)				
	2.00	17.50	30.00	300	½	23.0	
	2.50	19.50	34.00	300	¾	36.0	
	3.00	21.50	37.00	300	¾	47.0	
	4.00	26.00	43.00	175	¾	74.0	
	5.00	30.50	48.00	175	¾	111.0	
	6.00	36.50	55.00	175	¾	166.0	
	8.00	48.50	70.00	175	¾	341.0	
	10.00	60.50	74.50	175	¾	530.0	
	12.00	72.50	84.50	175	¾	773.0	

MOVEMENT CAPABILITY: +/- 8"

8" - 12" ID provided with two stainless steel braids.

PROJECT	
CUSTOMER	
ENGINEER	
REPRESENTATIVE	
DRAWING #	



4560 Buckley Road
Liverpool, NY USA 13088-2509
315/437-1611 • Fax 315/437-1903
www.flexhose.com • 1.877.TRI FLEX